

ELECTRIC DRIVE SYSTEM

- With a 30 horsepower electric motor, the RANGER EV provides quiet and clean operation with two hours of riding time.
- Range leader with High, Low, Max modes
- 40.2 km/h top speed
- 48–72 km range
- Battery charges using standard 240 outlet
- 650 Amp controller
- 48 Volt Brushless AC induction motor for low maintenance/high performance
- Quick charge kit available through PURE Polaris

HEAVY DUTY FRONT END PROTECTION


- Inset headlights for protection against rock chips & branches
- Most protection for front differential
- Dedicated vehicle tie down points

ROPS CERTIFIED CAB*

*OSHA ROPS 29CFR1928.53

CARGO BOX

- 226.8 kg capacity
Lock & Ride® box.



MACPHERSON STRUT FRONT SUSPENSION

- 20.3 cm of travel.



INDEPENDENT REAR SUSPENSION

- The long-travel Polaris Independent Rear Suspension (IRS) is the industry's smoothest ride with 20.3 cm front travel 22.9 cm rear travel and 25.4 cm of ground clearance.

ON DEMAND TRUE AWD w/VERSATRAC

- The Polaris On Demand All-Wheel Drive (AWD) system automatically engages when the rider needs more forward traction. It reverts to 2WD automatically when AWD is no longer needed.
- Drivers can easily switch to 1-wheel drive to produce extremely tight turns or minimise damage to sensitive terrain.



MODEL YEAR 2010 MODEL YEAR 2010 MODEL YEAR 2010 MODEL YEAR 2010 MODEL YEAR 2010 MODEL YEAR 2010 MODEL YEAR 2010

RANGER EV

QUIET. CLEAN. GREEN.

HARDEST WORKING FEATURES

- 30 hp electric motor
- Range leader with High, Low, Max modes
- 48 Volt Brushless AC high efficiency Induction motor for low maintenance
- 40.2 km/h top speed
- 226.8 kg cargo capacity
- 567 kg towing
- 453.6 kg payload
- On-Demand AWD with VersaTrac
- ROPS Certified cab*
- Cargo System

SMOOTHEST RIDING FEATURES

- Independent Rear Suspension (IRS)
- Class-leading suspension travel at 20.3 cm front travel and 22.9 cm rear travel
- High 25.4 cm of ground clearance
- Seating for two

COLOURS

- Boardwalk Blue
- Mossy Oak™ New Break-Up

NOTHING RIDES LIKE A  **POLARIS.**